

PRODUCT DATA SHEET

www.htm.co

Bituminous Waterproofing Membranes Co.
Kemalpasa Org. San. Bölgesi Mah. Gazi Bulvarı. No:
152 Kemalpaşa / İZMİR /TURKEY
Tel:+90 0232 877 04 02 (8 line)
Fax: +90 0232 877 04 10

ELS-100 ELASTOSOL

Document Number: PDS005 - 1

Publication Date :05th,Jan.2009 Revision date : 08.10.2017

PRODUCT DESCRIPTION	ELASTOSOL is a thermoplastic rubber-added, bitumen-solution based, single-component cold-applied waterproofing liquid It is used to prevent moisture in the floor and walls of the foundation and basement. Type I			
USAGE				
APPLICATION METHOD	Applied with brush. Please refer to application booklet.			
STORAGE	Pails stored away from direct sunlight			
ECOLOGICAL DATA	Can be used in natural atmosphere			
TEST	METHOD	UNIT	TOLERANCE	VALUES
Viscosity at 25°C	TS 103	сР	-	25 - 150
Water Content	TS 103	%	-	0
Distillation at 0-225 °C	TS 103	%	Min.	35
Distillation at 225-360 °C	TS 103	%	Max.	65
Residue Penetration at 25 ^o C (100 gr, 5s)	TS 103	dmm	±15	35
Matter soluble in trichloroethylene	TS 103	%	Min.	99
	-			
NPD = (No performance defined)				

NPD = (No performance defined)

* For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Material Safety Data Sheet