



www.btm.co

Bituminous Waterproofing Membranes Co.
Kemalpaşa Org. San. Bölgesi. Atatürk Mah. Gazi
Bulvarı. No: 152 Kemalpaşa / İZMİR /TURKEY
Tel:+90 0232 877 04 02 (8 line)
Fax: +90 0232 877 04 10

PRODUCT DATA SHEET

ELTW-400 ELASTOPAST WET

(Bituminous Mastic Sealant)

Document number :PDS-008-0
Publication Date :05th,Jan.2009 Revision date : -

PRODUCT DESCRIPTION	Cold applied rubber-modified bitumen joint sealer and adhesive			
USAGE	Sealing leaks and making repairs, fixing roofing felt overlaps and many other roofing, plumbing and waterproofing tasks for buildings. For waterproofing cracks and joints in dams and bridges. Waterproof finishing of overlaps, connections and joints of roof. Sticks to wet substrates (even under water)			
APPLICATION METHOD	Apply on clean surfaces at temperatures between +5 and +50 °C. In case of application in cold weather, keep cartridges at room temperature one day before the application. Oil products can dissolve the bitumen. So, usage of these components with ELTW 400 is not recommended. ELWT 400 can be applied with a handgun or a compressed airgun.			
PACKING	310 ml aluminium cartridge for use in standard sealant guns. 15 litre tins and 180 litre drums.			
STORAGE	Should not be stored in direct sunlight or a near a source of heat.			
ECOLOGICAL DATA	Can be used in natural atmosphere			
TEST	METHOD	UNIT	TOLERANCE	VALUES
Colour	-	-	-	black
Consistency	-	-	-	paste
Specific Gravity	-	gr/cm ³	min.	1,2
Resistance to flow at elevated temperature (70°C with 90° angle)	-	mm	-	No flow after 24 hours
Surface adhesion	-	-	-	pass
Curing time (depends on substrate)	-	weeks	-	1 -4

NPD = (No performance defined)

* For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Material Safety Data Sheet