

Certificate of Conformity of the Factory Production Control 2195-CPR-2517401

In compliance with Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation or CPR), this certificate applies to the construction

Products and systems for the protection and repair of concrete structures

BTM BİTÜMLÜ TECRİT MADDELERİ SAN. TİC. A.Ş.
Kemalpaşa Organize Sanayi Bölgesi Mah. Gazi Bulvarı No:152 Kemalpaşa/İzmir –
Turkey

produced by the manufacturer

BTM BİTÜMLÜ TECRİT MADDELERİ SAN. TİC. A.Ş.
Kemalpaşa Organize Sanayi Bölgesi Mah. Gazi Bulvarı No:152 Kemalpaşa/İzmir –
Turkey

and produced in the manufacturing plant

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard(s)

EN 1504-2: 2004

It is proof that the performance characteristics specified in the audit report numbered CPR-212/25, which is an integral part of this certificate and is annexed to this certificate under system 2+, are implemented and that all requirements of the Factory Production Control determined for these performances are compliant. This certificate was first issued on 23.06.2025 and will remain valid as long as neither the harmonised standard, the construction product, the assessment and verification of constancy of performance methods nor the manufacturing conditions and factory production control in the factory are modified significantly, unless suspended or withdrawn by the notified factory production control certification body. The certificate is supported through annual surveillance audit and is reissued after each surveillance audit.

Validity Date : 23.06.2029

Period Validity Date : 23.06.2026


Rukiye BALKAN
Deputy General Manager



FR. CPR. 24 R:05

Certificate of Conformity of the Factory Production Control 2195-CPR-2517401

Annex 1

Certification Scope:
BITULAST BTL200,
BTM ALFAHIBRIT
BTM ELASTO DRYROOF

Intended uses;
Prensip 1: Protection Against Ingress, Method 1.3. Coating;
Prensip 2: Moisture Control, Method 2.2 Coating;

Controlled Performance Characteristics;
- Capillary Absorption and Permeability to Water,
- Permeability to Water Vapour,
- Permeability to CO₂,
- Adhesion Strength by Pull-Off Test



Rukiye BALKAN
Deputy General Manager

FR. CPR. 24 R:05