



PRODUCT DATA SHEET

www.btm.co

Bituminous Waterproofing Membranes Co.
Kemalpaşa Org. San. Bölgesi Mah. Gazi Bulvarı. No:
152 Kemalpaşa / İZMİR /TURKEY
Tel:+90 0232 877 04 02 (8 line)
Fax: +90 0232 877 04 10

BTR-100

Document number :PDS-012-0

Publication Date :05th,Jan.2009 Revision date : -

PRODUCT DESCRIPTION	Cold applied bituminous waterproofing emulsion			
USAGE	Besides serving as primer at the waterproofing applications, are used to prevent humidity at the basement walls underground , to produce bituminous protective mortar. Type -1			
APPLICATION METHOD	Applied with brush. Please refer to application booklet.			
STORAGE	Pails stored away from direct sunlight			
ECOLOGICAL DATA	Can be used in natural atmosphere			
TEST	METHOD	UNIT	TOLERANCE	VALUES
Density	TS 113	gr/cm ³	±0,03	1,01
Water Content	TS 113	%	±5	65
Residue Content of Vaporization	TS 113	%	±5	35
Ash Content of Residue	TS 113	%	Min.	3
Strength of asphalt layer at the end of cure	TS 113	hours	Max.	24
Heating Test (at 100±3°C)	TS 113	-	-	No precipitation,flow or blister
Flammability	TS 113	-	-	No flame and burning
Flexibility (at 0±0.5°C)	TS 113	-	-	PASS

NPD = (No performance defined)

* For information and advice on the safe handling,storage and disposal of chemical products, users shall refer to the most recent Material Safety Data Sheet

The manufacturer serves the right to modify, at any time, the characteristics of its products

BF/14-17-0